



Never compromise on quality!



GRIPBOND PRO MAX

Ultimate Grab Adhesive

Description

The ultimate grab adhesive for a stronger longer lasting bond.

Properties

- ◆ For interior and exterior use
- ◆ Weather proof
- ◆ Solvent-free and odourless
- ◆ Quick curing
- ◆ Can be over painted
- ◆ Can be applied to wet surfaces

GRIPBOND PRO MAX typically has double the initial grab of most grab adhesives, eliminating the need for mechanical support in most applications. Typical bond strength: 250Kg/m². It has a high ultimate bond strength and is suitable for internal and external use, in all weather conditions. Superb adhesion qualities even on wet surfaces. Quick curing, weather resistant, isocyanate, solvent and acid-free making it safer to use. Remains fully elastic.

Uses

Suitable for use on metal, wood, glass, stone, polystyrene, concrete, plasterboard, insulation board, ceramics, polyester and many more surfaces.

Application

Ensure all surfaces are clean and free from grease, oil or any other contaminants that may hinder adhesion. Carefully cut the tip of the cartridge, taking care not to damage the threaded area. Screw on the "notched" nozzle attached and place cartridge in a standard sealant gun. Apply in beads or strips to one surface only, and bond the surfaces together carefully and allow to cure. Remove any uncured adhesive with white spirit.

Note: this product is not recommended for installations where joints are permanently immersed in water or on surfaces that bleed oils or plasticisers. If used on overhead applications, always use in conjunction with mechanical fixings. It is recommended for large mirrors but it should be used in conjunction with mechanical fixings. For large and/or heavy items provide temporary support until full cure is achieved. Not suitable for use on polypropylene or Teflon.

Overpaintable, however as quality and type of paint can vary,

Colour

Available in white.

Shelf Life

Use within 9 months. Store in original, unopened cartridge, in a cool, dry place at a temperature between +5°C and +25°C.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Safe Handling Precautions

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Curing in 24 hours	2.5mm
Bond Strength	250Kg/m ²
Shrinkage	Nil
Skinning Time	approx 10 minutes
Hardness Shore A (DIN 53505)	40+/-4
Temperature Resistance	-30°C to +95°C
Application Temperature	+5°C to +40°C
Storage Temperature	+5°C to +25°C

Container Sizes:

Colour:	White
Code:	BDPPROWH
Size:	EU3
Barcode:	5060021371409

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 7/6/17
Supersedes V1 30/11/16