

TECHNICAL DATA SHEET

BRIGHT

Thermostatic Recessed Three Control Shower Valve with Integral Twin Stopcocks

Product Specification

Product Code:	BRG SHC3STP C
Finish:	Chrome
Product Type:	Contemporary
Construction:	Body is of brass construction
Supply:	Suitable for all plumbing conditions, preferably balanced.
Inlet Connections:	15mm Compression connections
Working Pressures:	Min 0.2 Bar, Max 5.0 Bar

Additional Information

- Chrome plated to BS EN 248
- Suitable for cavities between 58-75mm
- Minimum cold water supply temperature is 5°C
- Maximum hot water supply temperature is 80°C
- Flow rate at 0.2 Bar (open outlet without flow regulators) is 9 l/min from stopcock. 12.9l/min from both outlet together
- The inlet hot water temperature must be at least 10% above the required blend temperature.
- Requires rear access to enable service to filters
- Cartridge can be accessed from front

Flow Rates (litres per minute)

System Pressure	0.2bar	0.5bar	1.0bar	2.0bar	3.0bar	5.0bar
BRG SHC3STP C - Outlet 1	7.7	14.2	20.7	29.27	35.85	46.29
BRG SHC3STP C - Outlet 2	7.3	14	20.8	29.42	36.03	46.51

Compliance/Approvals

WRAS Certificate No: 1407023

Technical Advice: For further information please call 0844 7016273 or email customer@bristan.com

Guarantee: 5 years covering manufacturing faults.

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG
 Telephone: 0844 701 6274 Facsimile: 0844 701 6275
 Web Site: www.bristan.com Email: enquire@bristan.com

